



FLARING WITH MONITORING

INVACOR offers the most custom, completely self-contained portable flare stacks in the industry. Our flare trailers are equipped with air assist flare tips to surpass industry requirements with a minimum 98% destruction efficiency rate while providing maximum air pressure for flaring virtually any type of pipeline product.

FLARE MONITORING REPORTS

30 TAC {115.726 (A)} {115.725 (M)}

Environmental compliance is easy with INVACOR'S monitoring and reporting packages. INVACOR monitors and records flare gas temperature, flare gas pressure, flare gas flow rate, calorific value (BTU content), and flare gas HRVOC content (gas chromatograph). To satisfy the site's requirements the monitoring data is compiled in a flare report. (Maximum 15 minutes between each reading & Analysis Report)

BENEFITS

- ▶ Experienced On-Site Flare Supervisors
- ▶ Hydraulically self-standing, trailer-mounted flare stacks for quick setup and teardown
- ▶ Completely Self Contained
- ▶ Ability to burn product in liquid or gas form
- ▶ One-of-a-kind air assist tip ensures smokeless flaring at high exit velocities
- ▶ Has air blower motors ranging from 1600 CFM up to 6400 CFM capabilities depending on the size of flare
- ▶ Can be outfitted to comply with current HRVOC standard contained in 30 TAC {115.726 (a)} {115.725(m)}
- ▶ All flares contain an inline swing check and flame arrestor, which are safety devices to prevent flash back
- ▶ If you have an emergency or need to schedule routine maintenance, our experienced staff is on hand 24 hours a day to answer all of your needs
- ▶ Accurate data collection of lost and unaccounted for gas via SCADA recording

VISIT OUR WEBSITE OR CONTACT US.

Phone: 979-848-1300

Fax: 979-848-1303

512 South Chenango Po Box 2200 Angleton, Texas 77515

www.INVACOR.com

